

## Article 8. Subdivision Design and Improvements

### 8.1 Purpose

Notwithstanding the following two provisions, this article is reserved. All additional references to this article shall apply to Chapter 9 of the Code of Ordinances, Subdivisions.

### 8.2 Zero Lot Line Construction

*Per Ordinance No. 2713 dated March 25, 2004.*

The following requirements apply to all single-family residential development.

#### A. Description

A zero lot line development is where houses in a development on a common street frontage are shifted or offset to one side of their lot. This provides for greater usable yard space on each lot. These developments require that planning for all of the house locations be done at the same time. Zero lot line developments are allowed by right. Review for compliance with the standards of this Section shall occur during the subdivision platting process. Restrictions that assure the minimum distance between houses and any required easements must be recorded on the plats of the applicable lots. Proof of such recordation must be submitted as part of the building permit application.

#### B. Setbacks

The side building setback shall be zero on one side of the house. This reduction does not apply to the street side setback or to the interior side setback adjacent to lots that are not part of the zero lot line project. The minimum distance between all buildings in the development must be fifteen feet.

*Per Ordinance No. 2713 dated March 25, 2004.*

#### C. Additional Standards

##### 1. Eaves

Eaves may project a maximum of 18 inches, excluding non-combustible gutters, over the adjacent property line.

*Per Ordinance No. 2713 dated March 25, 2004.*

##### 2. Maintenance Easement

A maintenance easement shall be dedicated between the two property owners to allow for maintenance or repair of the house built on the lot line. The easement shall be unobstructed, located on the adjacent property abutting the side wall and must be a minimum of seven and one-half feet in width. Required maintenance easements shall be shown on the recorded plat.

*Per Ordinance No. 2713 dated March 25, 2004.*

##### 3. Privacy

Windows or other openings that allow for visibility into the side yard of the adjacent lot are not allowed. Windows that do not allow visibility into the side yard of the adjacent lot, such as a clerestory window or a translucent window are allowed. All materials within three feet of the property line shall be fire-rated to meet building code requirements.

*Per Ordinance No. 2713 dated March 25, 2004.*

**8.3 Cluster Development**

A cluster development is a residential subdivision in which the lots are allowed to be smaller (in area and width) than otherwise required for the underlying, base zoning district, but in which the overall density cannot exceed the maximum density limit for the underlying zoning district. Through the cluster development option, a subdivision can contain no more lots than would otherwise be allowed for a conventional subdivision in the same zoning district, but the individual lots within the development could be smaller than required in a conventional subdivision. Smaller lot sizes within a cluster development are required to be offset by a corresponding increase in open space.

**A. Conflict with Other Regulations**

If there is a conflict between the cluster development standards of this Section and any other requirement of this UDO, the standards of this Section control. Where no conflict exists, a cluster development is subject to all other applicable requirements of this UDO.

**1. Where Allowed**

Cluster developments are allowed in all zoning districts.

**2. Approval Procedure**

Cluster Developments are subject to the subdivision procedures set forth in herein.

**3. Lot Size**

There is no set minimum lot width or depth requirement within a cluster development; however, the lot size (area) may be reduced by up to 25 percent as long as individual lot sizes are adequate to meet all required density, district, and development standards.

**4. Setbacks and Building Separations**

The minimum setback standards of the base zoning district apply along the perimeter of a cluster development. All detached structures within a cluster development must be separated by a minimum distance of ten feet.

**5. Open Space**

**a. On-Site Open Space**

Cluster developments shall be subject to the minimum on-site open space standards of the base zoning district, if applicable.

**b. Common Open Space**

**(1) Minimum Requirement.** Common open space is required within a cluster development to ensure that the overall density within the development does not exceed the maximum density allowed by the underlying zoning district. Common open space must be provided in an amount at least equal to the difference between:

- (a)** The actual, average lot area per dwelling unit within the cluster development; and
- (b)** The required lot area per dwelling unit for conventional development within the underlying base zoning district.

- (2) **Use of Common Open Space.** Common open space must be set aside and designated as an area where no development will occur, other than project-related recreational amenities or passive open space areas. The Planning and Zoning Commission may require that up to 50 percent of required common open space be useable recreational space, if deemed necessary by the Planning and Zoning Commission to ensure adequate recreational amenities for residents of the development.